



ASPROC SEPARON™ DESANDING HYDROCYCLONE

& +39 055 9705134 🖂 info@asproc.net

⊕ www.asproc.net





Separon[™] Desanding Hydrocyclone

Solids Handling



Designed to meet the harsh conditions of the upstream process, Separon[™] Desanding Hydrocylones achieve efficient solids separation while managing pressure drop. The number of operating liners is determined by the system differential pressures and flow rates to maximize efficiency.

HOW IT WORKS

The Separon Desanding Hydrocylone achieves cyclonic separation of solids using energy from the flow stream. Flow direction changes force the fluid to spin in a radical vortex pattern. As the internal diameter is reduced over the length of the cyclone, the vortex flow is accelerated and separation occurs. Heavier material moves to the outside while lighter material moves to the core. Solids as fine as 5 microns are removed by exiting into an accumulation chamber.

KEY BENEFITS

Cost Saving

 Roboust design and weat resistant reaction bonded silicon carbide offers a long life with less maintenance and OPEX

Better Performance

- Closely packed liners within the vessel produce finer separations than other hydrcyclones in the market
- Uses involute inlet geometry to minimize fluid turbulance and reduce inlet wear

High Flexibility

- Compact design for reduced footpring and weight
- Flexible operation for variations in rates
- Installation options for easy retrofit and piping
- Availbale as standalone equipment or complete skid packages



STANDARD FEATURES

 ASME code stamped (Div i & Div II)

MATERIALS OF CONSTUCTION

- Vessel: Carbon Steel, Stainless Steel, or Duplex Stainless Steel
- Cyclones: Reaction Bonded Silicon Carbide

COMMON APPLICATIONS

- Wellhead upstream of the choke (up to 15,000 psi, multiphase systems, and 100% gas flow)
- Downstream of the choke and before the production separator (wellstream)
- From the separator in the aqueous phase or sand jetting effluent
- Secondary Recovery
- Primary separation of solids from production separators
- Primary and Secondary Produced Water Treatment
- Offshore Production

This brochure is intended for general information purposes only and is not intended as a representation or warranty of any kind., or as a statement of any terms or conditions of sale. The information herin is believed to be correct, but is not warranted for correctness or completeness, or for applicability to any particular customer or situation.

© 2020 Exterran Corporation. All Rights Reserved

Separon[™] Desanding Hydrocyclone Solids Handling



NOTES

For more information please email us at info@asproc.net



